KODAK FLEXCEL NX

SYSTEM

A Full Portfolio	Plate sizes						
System Type	610 x 762 mm 24 x 30 inch	800 x 1067 mm 31.5 x 42 inch	900 x 1200 mm 35.4 x 47.2 inch	1067 x 1524 mm 42 x 60 inch	1270 x 1651 mm 50 x 65 inch	1270 x 2032 mm 50 x 80 inch	
KODAK FLEXCEL NX Wide 5080 System	x	х	x	x	x	х	
KODAK FLEXCEL NX Wide 4260 System	x	х	x	x			
KODAK FLEXCEL NX Wide 3548 System	х	х	х				
KODAK FLEXCEL NX Mid System	x	x					
KODAK FLEXCEL NX Narrow System	х						



^{© 2018} Kodak, Kodak, DigiCap, Flexcel, Squarespot and the Kodak Logo are trademarks of Kodak Subject to technical change without notice. 180616

KODAK.COM/GO/FLEXCELNX



Compact and Mighty

The KODAK FLEXCEL NX System has a serious advantage. One that goes beyond the traditional capabilities of flexo. It's flexo without compromise. Ready to compete?

Meet the KODAK FLEXCEL NX Mid/Narrow Imager. With a smart footprint and the latest hardware, it delivers exceptional speed and surprising versatility for reliable small format applications. And for imaging both flexo and thermal offset plates, the Hybrid Option nicely maximizes your time and investment.

Unmatched technology.

You want unsurpassed quality output with zero impact on productivity. Kodak's unique imaging technology gives you the powerful NX Advantage that sets you up for guaranteed success on press. And with KODAK SQUARESPOT Imaging Technology, impeccable process control is yours. Consistent, efficient, compelling. What quality gap?

Looking for the fastest imaging speed in the industry? FLEXCEL NX Imagers expose the KODAK FLEXCEL NX Thermal Imaging Layer at breathtaking speed. Expect highly efficient and cost-effective plate making. On repeat.

Rich capabilities.

Versatile products and proven technologies that can adapt quickly to shifting markets are the rule. Already a robust platform, enhancements to the FLEXCEL NX System are backwards compatible. Outstanding imaging technology, impressive productivity and process stability along with easy maintenance - a solid ROI.

Complete solution.


With innovative hardware, software, and consumables designed to work seamlessly together, the KODAK FLEXCEL NX System delivers one powerful performance. Along with Kodak's world-class service and support, you have a bestin-class solution to deliver high-definition flexo printing that exceeds expectations. Even yours.


It's flexo. Transformed.













Complete integration.

FLEXCEL NX Mid/Narrow Imager

Easy to use and semi-automatic with impressively fast imaging, it's designed to work exclusively with KODAK FLEXCEL NX Plate Kits. And for a process-free alternative to conventional silver halide film, it's fully compatible for KODAK DITR Film imaging.

FLEXCEL NX Laminator

Quick and simple lamination of the FLEXCEL NX Thermal Imaging Layer to the FLEXCEL NX Plate prior to exposure and processing removes all oxygen between mask and plate for full-amplitude flat top dots. Crystal clear difference.

FLEXCEL NX Workstation

Includes KODAK TIFF Assembler Plus Software, fully loaded and feature-rich for managing plate layouts, deploying Kodak's powerful NX Advantage technology, and supporting third-party cutting tables.

Powered by NX Advantage

Kodak's NX Advantage technology, that includes patented Advanced Edge Definition, is unique to the FLEXCEL NX System and gives flexo printers an unprecedented level of control over ink transfer during the printing process, resulting in substantial print production efficiency and quality benefits with a simple plate portfolio.

Powered by SQUARESPOT

KODAK SQUARESPOT Imaging Technology is Kodak's award-winning thermal imaging technology, available only in Kodak imaging devices. SQUARESPOT Technology allows printers to reach a higher level of stability, accuracy, and reliability in their printing operation.

KODAK FLEXCEL NX

MID/NARROW SYSTEM

Workflow Specifications								
Workflow connectivity	KODAK TIFF Assembler Plus Software; accepts 1 bit TIFF and LEN files from all workflows systems.							
Specifications for imaging KOD	AK FLEXCEL NX The	rmal Imaging Layer (TIL)					
Imaging speed	With DIGICAP NX Patterning applied:13.5 m²/ hr Without DIGICAP NX Patterning applied:12.5 m²/ hr							
Media sizes and throughput * (includes loading and unloading)	TIL size	For plate size	Mid	Narrow	Sheets imaged per hour@ 2400 dpi with DIGICAP NX			
	640 x 838 mm (25.2 x 33 in),	610 x 762 mm (24 x 30 in)	Х	х	18			
	838 x 1097 mm (33 x 43.2 in)	800 x 1067 mm (31.5 x 42 in)	х		12			
Resolution	2400 dpi							
Repeatability	± 8 microns between 2 consecutive exposures on the same TIL left on the drum							
	1							
Finished Plate Resolution	300 lpi maximum linescreen (0.4% to 99.6%)							
Physical Characteristics for ima		(00 70 40:)						
Dimensions (H x W x D)	160 x 200 x 120 cm (63 x 79 x 48 in)							
Weight	Imager: 650 kg (1433 lb)							
Physical Characteristics for lam Dimensions (H x W x D)		(2E 4 v 71 2 v 42 4 in)						
Weight	90 x 181 x 110 cm (35.4 x 71.3 x 43.4 in.)							
Operating conditions	350 kg (770 lb)							
Temperature	17°- 30°C (63° - 86°F)							
Humidity	40% - 60% relative humidity, non-condensing							
Optional Upgrades	1370 0070101011	o Harrialty, Horr condc						
	Enables the imaging of thermal offset plates							
Hybrid Option	Enables the image	ing of thermal offset b	lates					

High resolution imaging option 9600 X 4800 dpi

Provides Kodak screening options compatible with any prepress workflow

KODAK FLEXCEL NX System is compatible with KODAK DITR Film.

KODAK FLEXCEL NX Screening

Resolution Upgrade

Tower

Accessories



Densitometer
Standard with every
FLEXCEL NX System,
the X-RITE 361T UV
Densitometer is a
quality control tool for
imaging set-up and
troubleshooting.



Media Rack
Convenient, mobile, and
designed to be placed
adjacent to the NX Mid/
Narrow Imager to ensure
easy media handling.



Rolling Plate Cart
Smartly designed to
tilt and move for easy
transportation of wide
format plates between
lamination, exposure,
and processing
stations